



Shelf Life of Industrial Products

The shelf life of all PANG materials is greatly dependent on the storage conditions. Temperatures below 75°F (24°C) are recommended and the materials must be stored out of direct sunlight.

1 Year Shelf Life	
Item Number	Item Description
PANGOFOL	
992 (incl. /QT, /GAL, /5GAL, /55GAL)	PANGOFOL BLACK NON-FLAMMABLE
992F (incl. /8OZ, /PT, /QT, /GAL, /5GAL, /55GAL)	PANGOFOL BLACK FLAMMABLE
993F (incl. /QT, /GAL, /5GAL, /55GAL)	PANGOFOL WHITE FLAMMABLE
PANGKIT, PANGKITF	PANGOFOL KIT (992 or 992F/QT and 968F/60CC)
CUSHION GUM	
LC, LM, LN, LR/10#, LT, LX	Low Temp. Cure / L-Series gums such as LM, LN, etc.
RA, RC, RN, RR, RU, RX	REG CURE REPAIR GUM
849, 850, 861, 862, 863, 864, 867, 868, 869, 870	VULGUM
854	CHEMICAL CURE GUM 1 LB. ROLL
855	HEAT VUL-GUM, 1 LB. ROLL
HT8 or 16 or 32	GUM

18 Month Shelf Life	
Item Number	Item Description
968F (inc. /15CC, /30CC, /60CC)	ACTIVATOR
PPANGKIT1	PLASTOPANG KIT (1090F/8OZ W/968F/15CC)
PPANGKIT2	PLASTOPANG KIT (1090F/QT W/968F/60CC)
GH200 or 218	GHC GUM

2 Year Shelf Life	
Item Number	Item Description
CHEMICALS	
658F (inc. /8OZ, /GAL, /55GAL, FG)	BLUE MAXIBOND CEMENT FLAMMABLE
CA32	CITRUS CLEANER
608F (inc. 8OZ, /QT, /55GAL)	SUPERSOLUTION FLAMMABLE
708F (inc. /8OZ, /QT, /GAL, /55GAL, L)	HEAVY DUTY SOLUTION FLAMMABLE
1090F (inc. /8OZ, /QT, /QTS, /GAL, /5GAL, /53GAL)	PLASTOPANG
REPAIR MATERIALS	
DP5-DP20	DIAMOND PATCH
NDP5-NDP20	DIAMOND PATCH
FR1510 or FR909N60	ELI-FLEX
110FP-SET/1LB	PANGIT A&B 2 LB SET FLAMMABLE
120FP-SET/2LB	PANGIT A&B 4LB SET FLAMMABLE
PLC (inc. 10LF, 15LF)	RECT PATCH
NPL (inc. 10LF, 15LF)	REPAIR STRIP
CTGS/BX15	CHEMICAL TIE GUM

For more information, contact your PANG Industrial Sales Representative or PANG Industrial Customer Service.
1-800-705-2206 • 1-740-967-9015 • Fax: 740-967-1039 www.PANGindustrial.com



Shelf Life of Industrial Products

The shelf life of all PANG materials is greatly dependent on the storage conditions. Temperatures below 75°F (24°C) are recommended and the materials must be stored out of direct sunlight.

3 Year Shelf Life	
Product Name/Item Number	Item Description
CHEMICAL	
Rapid Solution/RS3F (includes QT/GAL/5GAL/55GAL)	Black flammable heat cure cement
SHEET RUBBER WITH BONDING LAYER	
PANGWEAR 35 with bonding layer - all thickness	Orange 35 durometer NR blend with neoprene bonding layer
PANGWEAR 45 with bonding layer - all thickness	Red 45 durometer NR blend with neoprene bonding layer
PANGUARD 60 with bonding layer - all thickness	Black 60 durometer NR blend with neoprene bonding layer
PANGUARD 60FE with bonding layer - all thickness	Black 60 durometer MSHA flame resistant rubber w/ neoprene bonding layer
PANGLAG 60 with bonding layer - all thickness	Black 60 durometer NR blend with neoprene bonding layer
PANGLAG 60FE with bonding layer - all thickness	Black 60 durometer MSHA flame resistant rubber w/ neoprene bonding layer
PANGRIP CERAMIC LAGGING - all thickness	Black 60 duro. ceramic lagging w/ neoprene bonding layer
PANGRIP CERAMIC LAGGING FE - all thickness	Black 60 duro. ceramic lagging MSHA flame resistant w/ neoprene bonding layer

5 Year Shelf Life	
Product Name/Item Number	Item Description
REPAIR MATERIALS	
Air Tool Oil /753	Lubricant oil for pneumatic tools
Silver Ink Pen/SIP	Sharpie silver all surface marker
All Surface crayons, markers, paintsticks/ 948, 951,946WY,947WY	White and yellow crayons, markers, paintsticks
SHEET RUBBER WITHOUT BONDING LAYER	
PANGWEAR 35 without bonding layer - all thickness	Orange 35 durometer NR blend with neoprene bonding layer
PANGWEAR 45 without bonding layer - all thickness	Red 45 durometer NR blend no bonding layer
PANGUARD 60 without bonding layer - all thickness	Black 60 durometer NR blend no bonding layer
PANGUARD 60FE without bonding layer - all thickness	Black 60 durometer MSHA flame resistant rubber no bonding layer
PANGSKIRT 45 - all thickness and widths	Orange 45 durometer NR blend
PANGSKIRT 50 - all thickness and widths	Blue 50 durometer NR blend

For more information, contact your PANG Industrial Sales Representative or PANG Industrial Customer Service.
1-800-705-2206 • 1-740-967-9015 • Fax: 740-967-1039 www.PANGindustrial.com